

HANDLE-TECH

PowerGrip Series

Handle-Tech is Your
#1 SAFETY TOOL

Part Number	Description	Fits Hose & Pipe Size (Outside Diameter)
PowerGrip 200	200SUC/PIPE handle w/ Grip Pads and BoltGuard Pad pre-installed	1.4" - 2.4"
PowerGrip 300	300PIPE handle w/ Grip Pads and BoltGuard Pad pre-installed	2.4" - 3.525"
PowerGrip 400	400PIPE handle w/ Grip Pads and BoltGuard Pad pre-installed	3.65" - 4.65"
PowerGrip 500	500PIPE handle w/ Grip Pads and BoltGuard Pad pre-installed	4.65" - 5.65"
PowerGrip 600	600PIPE handle w/ Grip Pads and BoltGuard Pad pre-installed	5.65" - 6.65"
PowerGrip 700	700PIPE handle w/ Grip Pads and BoltGuard Pad pre-installed	6.65" - 7.65"
PowerGrip 800	800PIPE handle w/ Grip Pads and BoltGuard Pad pre-installed	7.65" - 8.65"
PowerGrip 900	900PIPE handle w/ Grip Pads and BoltGuard Pad pre-installed	8.65" - 9.65"
PowerGrip 1000	1000PIPE handle w/ Grip Pads and BoltGuard Pad pre-installed	9.65" - 10.65"
Safety Lock	Accessory - prevents accidental release of the latch	
Spare Handle	Accessory - straight handle that screws into pipe handle	
ErgoGrip Spare Handle	Accessory - 90° handle that screws into pipe handle	



The Handle-Tech PowerGrip Series combines our Pipe Handle, Grip Pads, and BoltGuard Pad into a complete handling solution.

Engineered for safety, strength, and reliability, the PowerGrip Series delivers superior control, traction, and protection when working with pipe, hose, or tubing ranging from 2" to 10" in diameter.

- Ergonomic Handle-Tech Pipe Handle provides superior leverage and handling control
- Grip Pads deliver textured, slip-resistant traction—even on smooth or wet surfaces
- Stainless steel BoltGuard Pad prevents bolt contact damage to adjacent components
- Complete system reduces strain, enhances safety, and increases handling precision
- Available in multiple sizes from 2" to 10"

**BUY HANDLE-TECH
HANDLES TODAY!**

Contact Nikki Prussman

Email: nikki@handle-tech.com

Phone: 610-385-6091 ext. 241

SEE OUR PRODUCTS IN ACTION!

Visit: www.handle-tech.com



SPECS & CONSTRUCTION MATERIAL INFORMATION

All our standard handles are composed of Long Glass Nylon which enhances the thermal properties compared to commonly used materials such as aluminum; in addition, this lightweight material is stronger and more wear-resistant. From temperatures of -40C to +50C, each handle is designed to battle the most hostile environments. The Handle-Tech Handle has a safe lifting capacity of 400lbs with a breaking point at 1125 lbs.

*Note that this device was designed for hand-use only and should only be used as designed. The following specifications apply to all Handle-Tech handles.

MECHANICAL PROPERTIES	METRIC	ENGLISH	COMMENTS
Hardness, Rockwell M	88.0 - 100	88.0 - 100	Average value: 94.0 Grade Count:4
Hardness, Rockwell R	115 - 122	115 - 122	Average value: 120 Grade Count: 16
Tensile Strength, Ultimate	165 - 318 MPa	23900 - 46100 psi	Average value: 237 MPa Grade Count:21
	127 - 353.701 MPa, @Temperature -40.0 - 121 °C	18400 - 51300.1 psi, @Temperature -40.0 - 250 °F	Average value: 147 MPa Grade Count:3
	95.0 - 130 MPa @Temperature 130 - 175 °C	13800 - 18900 psi @Temperature 266 - 347 °F	Average value: 147 MPa Grade Count:2
	95.0 - 130 MPa @Time 1.80e+7 - 7.20e+7 sec	13800 - 18900 psi @Time 5000 - 20000 hour	Average value: 147 MPa Grade Count:2
Tensile Strength, Yield	148 - 285 MPa	21500 - 41300 psi	Average value: 223 MPa Grade Count:21
	144.79 - 144.79 MPa @Temperature 93.3 - 93.3 °C	21000 - 21000 psi @Temperature 200 - 200 °F	Average value: 145 MPa Grade Count:1
Elongation at Break	1.20 - 4.00 %	1.20 - 4.00 %	Average value: 1.99 % Grade Count:37
	1.80 - 2.20 % @Temperature -40.0 - 121 °C	1.80 - 2.20 % @Temperature -40.0 - 250 °F	Average value: 1.98 % Grade Count:2
Modulus of Elasticity	10.3 - 23.2 GPa	1500 - 3360 ksi	Average value: 18.9 GPa Grade Count:20
	11.9 - 20.8566 GPa @Temperature -40.0 - 121 °C	1730 - 3025.05 ksi @Temperature -40.0 - 250 °F	Average value: 14.9 GPa Grade Count:2
Flexural Yield Strength	234 - 460 MPa	33900 - 66700 psi	Average value: 350 MPa Grade Count:39
	260 - 260 MPa @Temperature 80.0 - 80.0 °C	37700 - 37700 psi @Temperature 176 - 176 °F	Average value: 260 MPa Grade Count:1
Flexural Modulus	0.461 - 22.8 GPa	66.9 - 3300 ksi	Average value: 17.4 GPa Grade Count:39
	0.227527 - 19.3053 GPa @Temperature -40.0 - 121 °C	33.0005 - 2800.04 ksi @Temperature -40.0 - 250 °F	Average value: 9.78 GPa Grade Count:4
Izod Impact, Notched	0.950 - 6.62 J/cm	1.78 - 12.4 ft-lb/in	Average value: 2.27 J/cm Grade Count:33
	1.30 - 7.68816 J/cm @Temperature -40.0 - 149 °C	2.44 - 14.4031 ft-lb/in @Temperature -40.0 - 300 °F	Average value: 4.51 J/cm Grade Count:2
Izod Impact, Unnotched	10.7 - 5340 J/cm	20.0 - 10000 ft-lb/in	Average value: 26.4 J/cm Grade Count:16
Izod Impact, Notched (ISO)	11.0 - 30.0 kJ/m²	5.23 - 14.3 ft-lb/in²	Average value: 15.8 kJ/m² Grade Count:3
Charpy Impact Unnotched	6.50 - 15.0 J/cm²	30.9 - 71.4 ft-lb/in²	Average value: 10.0 J/cm² Grade Count:9
	6.00 - 9.70 J/cm² @Temperature -40.0 - 30.0 °C	28.6 - 46.2 ft-lb/in² @Temperature -40.0 - 86.0 °F	Average value: 8.05 J/cm² Grade Count:7
Charpy Impact, Notched	1.30 - 5.40 J/cm²	6.19 - 25.7 ft-lb/in²	Average value: 2.68 J/cm² Grade Count:9
	1.20 - 4.60 J/cm² @Temperature -30.0 - 30.0 °C	5.71 - 21.9 ft-lb/in² @Temperature -22.0 - 86.0 °F	Average value: 1.88 J/cm² Grade Count:6
Dart Drop, Total Energy	7.85 - 16.4 J @Temperature -20.0 - -20.0 °C	5.79 - 12.1 ft-lb @Temperature -4.00 - -4.00 °F	Average value: 12.1 J Grade Count:1
	7.85 - 16.4 J @Thickness 3.18 - 3.18 mm	5.79 - 12.1 ft-lb @Thickness 0.125 - 0.125 in	Average value: 12.1 J Grade Count:1

ELECTRICAL PROPERTIES	METRIC	ENGLISH	COMMENTS
Electrical Resistivity	1.00e+9 - 1.00e+16 ohm-cm	1.00e+9 - 1.00e+16 ohm-cm	Average value: 6.94e+14 ohm-cm Grade Count:15
Surface Resistance	1.00e+10 - 1.00e+16 ohm	1.00e+10 - 1.00e+16 ohm	Average value: 8.50e+14 ohm Grade Count:12
Dielectric Strength	19.7 - 22.0 kV/mm	500 - 559 kV/in	Average value: 19.9 kV/mm Grade Count:14

THERMAL PROPERTIES	METRIC	ENGLISH	COMMENTS
CTE, linear	10.0 - 27.0 µm/m-°C	5.56 - 15.0 µin/in-°F	Average value: 21.5 µm/m-°C Grade Count:18
Thermal Conductivity	0.300 - 0.548 W/m-K	2.08 - 3.80 BTU-in/hr-ft²-°F	Average value: 0.424 W/m-K Grade Count:4
Melting Point	220 - 262 °C	428 - 504 °F	Average value: 253 °C Grade Count:11
Deflection Temperature at 0.46 MPa (66 psi)	220 - 262 °C	428 - 504 °F	Average value: 254 °C Grade Count:11
Deflection Temperature at 1.8 MPa (264 psi)	210 - 263 °C	410 - 505 °F	Average value: 251 °C Grade Count:37
Flammability, UL94	HB	HB	Grade Count:12

Custom Handles: Custom sizes include some parts made from High Density Polyethylene (HDPE) and/or carbon fiber infused Polyethylene Terephthalate Glycol (PETG). Other requested materials can be used including Aluminum, Nylon, PVC, or Polypropylene, all with various material properties and priced at the time of order. Although this process is more expensive than ejection molding, these different materials can provide unique handle properties (high acid, extreme heat etc.). All the custom handles use common parts from the Handle-Tech product line. Only the front and rear curves are made from new materials. We will build molds for ejection molding long glass nylon as soon as quantities are at a level where we can justify the high cost involved with making permanent molds.

Contact Nikki Prussman

Email: nikki@handle-tech.com

Phone: 610-385-6091 ext. 241